



PAB-12WP/SW

Order No.: 0253740

PRODUCTINFOS

Weatherproof PA speakers with IP classification.

Exactly the right speakers whenever a high sound quality, a high volume capability and a respective resistance to all weather conditions are required. Ideally suited for permanent open-air applications, e.g. at fairground attractions, PA applications in pedestrian areas, at sports facilities and wherever a weather-protected installation of the speakers is not possible.

Weatherproof high-performance PA speaker system, 200 W, 8 Ω

- High-performance 2-way bass-reflex system in an ABS cabinet
- 30 cm (12") PA bass speaker with impregnated paper cone
- 25 mm (1") horn tweeter system
- Excellent sound characteristics
- Front grille with water-repellent gauze
- SPEAKER in and parallel out
- Metal parts made of stainless steel
- 4 x M10 threaded insert each at the top and bottom for suspended installation
- Stand sleeve
- Ball-proof according to DIN 18032, Part 3

Production Partner 04/2012

“With the PAB-12WP/SW, the product range of IMG Stage Line now includes a weatherproof (IP45) 12/2 speaker system. It is available at an attractive price yet has plenty to offer. The speaker system provides impressive test results and a great sound experience. Overall, the PAB-12WP/SW and the PAB-120WP/SW can definitely be recommended for purchase, especially if you need a solid 12/2 speaker system which is able to still operate effectively even under difficult boundary conditions.” Test author Anselm Goertz

tools4music 02/2012

“[...] for users and service providers who are often working at outdoor events or have to attend permanent outdoor applications, the PAB-12WP/SW is definitely worth considering ... open-air event in the Rhineland area, Germany ... continuous rain, from light drizzle to downpour ... despite plenty of water, even from every angle, the PAB-12WP/SW provided a smooth performance throughout the 6-hour test. Soaking wet on the outside, bone-dry on the inside.”

- + Pleasant sound - with impressive power reserves
- + Truly waterproof
- + Practice-orientated handling
- + Good workmanship

TECHNICAL SPECIFICATIONS

PAB-12WP/SW

| | |
|--------------------------------|------------------------------------|
| Active/passive | passive |
| Transmission technology | cable |
| Total power rating | 400 W |
| Power rating (RMS) | 200 W |
| Impedance | 8 Ω |
| Frequency range | 42-20,000 Hz |
| System | 2-way bass-reflex |
| Bass speaker | 30 cm (12") PA bass speaker |
| Tweeter | 25 mm (1") horn tweeter |
| Number of speakers | 2 |
| Speaker size | 30 cm (12") |
| SPL | 98 dB/W/m |
| Max. rated SPL | 121 dB |
| Housing material | ABS plastic |
| Colour | black |
| Mounting device | M10 threaded inserts, stand sleeve |
| Protected against ball rebound | yes |
| Protection class | IP45 |

PAB-12WP/SW

| | |
|--------------------------------|-----------------------|
| Admiss. ambient temp. | -10 °C to +40 °C |
| Dimensions | 370 x 655 x 410 mm |
| Width | 370 mm |
| Height | 655 mm |
| Depth | 410 mm |
| Weight | 20.32 kg |
| Inputs | 1 x SPEAKER |
| Outputs | 1 x SPEAKER, par. out |
| Packing dimensions (W x H x L) | 0.47 x 0.73 x 0.43 m |
| Gross weight | 25.36 kg |
| Net weight | 20.32 kg |